

Tapered roller bearing 32322-JR-JTEKT - 32322-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32322-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
110	240	84.5	80	65	691	943			1 600	2 200	32322JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
26D	59.3	128	137	226	198	222	9	19.5	3	2.5	0.35	1.74	0.96	17.8

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411330
Inside diameter	110 mm
Outside diameter	240 mm
Thickness	84.5 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE