

Tapered roller bearing 32924-JR-JTEKT - 32924-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32924-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
120	165	29	29	23	172	298	2 100	2 700			32924JR			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
20C	29.4	129	128	156	152	160	6	6	1.5	1.5	0.35	1.72	0.95	1.77

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125652
Inside diameter	120 mm
Outside diameter	165 mm
Thickness	29 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE