

## Tapered roller bearing T4CB120-JTEKT - T4CB120-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/t4cb120-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0e</sub>	C <sub>0i</sub>	Grease lub.	Oil lub.				
120	170	27	25	19.5	3	3	184	262	2 000	2 700	T4CB120			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4CB	34.6	134	130	156	155	164	4	7.5	2.5	2.5	0.47	1.27	0.70	1.78

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411354
Inside diameter	120 mm
Inside diameter	4.724" inch
Outside diameter	170 mm
Outside diameter	6.693" inch
Thickness	27 mm
Thickness	1.063" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE