

# Tapered roller bearing 33024-JR-JTEKT - 33024-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33024-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
120	180	48	48	38	299	540	2 000	2 600	33024JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2DE	36.2	132	132	170	160	171	6	10	2	2	0.31	1.97	1.08	4.16

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126079
Inside diameter	120 mm
Outside diameter	180 mm
Thickness	48 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE