

## Tapered roller bearing 32324-JR-JTEKT - 32324-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32324-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                      |      |
| 120                                    | 260                | 90.5                     | 86                   | 69                      | 4                    | 3                    | 800                  | 1 110                                | 1 500                | 2 000                     | <b>32324JR</b>     |                |                      |      |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | d <sub>2a</sub> min.    | d <sub>2a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 260                                    | 62.7               | 138                      | 148                  | 246                     | 213                  | 239                  | 9                    | 21.5                                 | 3                    | 2.5                       | 0.35               | 1.74           | 0.96                 | 22.2 |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 4549250125355 |
| Inside diameter  | 120 mm        |
| Outside diameter | 260 mm        |
| Thickness        | 90.5 mm       |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE