

## Tapered roller bearing 32956-JR-JTEKT - 32956-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32956-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
280	380	63.5	63.5	48	3	2.5	780	1630	770	1000	32956JR			
Dimension series to ISO995 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	S <sub>2a</sub> min.	S <sub>2a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4EC	75.1	294	298	368	347	368	11	15.5	2.5	2	0.43	1.39	0.76	20.14

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125812
Inside diameter	280 mm
Outside diameter	380 mm
Thickness	63.5 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE