

# Tapered roller bearing 32056-JR-JTEKT - 32056-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32056-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.					
280	420	87	87	65	1200	2280	720	960			32056JR				
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	r <sub>2a</sub> min.	r <sub>2a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
4FC	91.1	302	305	402	370	402	14	22	4	3	0.46	1.31	0.72	41.7	

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123832
Inside diameter	280 mm
Outside diameter	420 mm
Thickness	87 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE