

Tapered roller bearing 30256-JTEKT - 30256-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30256-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
280	500	89	80	67	1260	1920	610	610	30256					
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	96.2	308	325	478	440	475	14	21	5	4	0.42	1.44	0.79	67.5

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412030
Inside diameter	280 mm
Outside diameter	500 mm
Thickness	89 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE