

Tapered roller bearing 32256-JTEKT - 32256-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32256-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
280	500	137	130	106	1860	3150	610	610	32256	

Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	117.2	308	325	478	420	474	16	30	5	4	0.43	1.39	0.77	108

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412047
Inside diameter	280 mm
Outside diameter	500 mm
Thickness	137 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE