

## Tapered roller bearing 32964-JR-JTEKT - 32964-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32964-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                      |            |                                   |                                   |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|--------------------------------------|----------------------|---------------------------|----------------------|------------|-----------------------------------|-----------------------------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>                      | Grease lub.          |                           | Oil lub.             |            |                                   |                                   |                      |      |
| 320                                    | 440                | 76                       | 76                   | 57                      | 1 060                | 2 270                                | 640                  | 850                       | 32964JR              |            |                                   |                                   |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                                      |                      |                           |                      |            |                                   |                                   |                      |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min.                 | S <sub>1a</sub> max. | r <sub>1a</sub> min.      | r <sub>1a</sub> max. | Constant e | Axial load factors Y <sub>1</sub> | Axial load factors Y <sub>0</sub> | (Refer. 1) Mass (kg) |      |
| 3FD                                    | 85.0               | 338                      | 342                  | 426                     | 401                  | 426                                  | 12                   | 19                        | 3                    | 2.5        | 0.42                              | 1.44                              | 0.79                 | 34.0 |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952412085 |
| Inside diameter  | 320 mm        |
| Outside diameter | 440 mm        |
| Thickness        | 76 mm         |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE