

Tapered roller bearing 32064-JR-JTEKT - 32064-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32064-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.							
320	480	100	100	74	1 510	2 810	600	800	32064JR						
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
4GD	103.0	342	344	462	418	461	16	26	4	3	0.46	1.31	0.72	58.7	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250306822
Inside diameter	320 mm
Outside diameter	480 mm
Thickness	100 mm
Weight	58700 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE