

Tapered roller bearing 32228-JR-JTEKT - 32228-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32228-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
140	250	71.75	68	58	636	961			1 500	2 000	32228JR			
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4FD	60.0	158	158	236	210	238	9	13.5	3	2.5	0.44	1.38	0.76	14.7

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419800
Inside diameter	140 mm
Inside diameter	5.512" inch
Outside diameter	250 mm
Outside diameter	9.843" inch
Thickness	71.75 mm
Thickness	2.825" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE