

Tapered roller bearing 30328-JR-JTEKT - 30328-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30328-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
140	300	67.75	62	53	749	962	1 300	1 700	30328JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{2a} max.	D _{1a} max.	D _{2a} min.	S _{1a} min.	S _{2a} min.	r _{3a} min.	r _{4a} max.		Y ₁	Y ₀		
2GB	56.9	162	179	282	254	273	10	14.5	4	3	0.35	1.74	0.96	22.6

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419824
Inside diameter	140 mm
Outside diameter	300 mm
Thickness	67.75 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE