

## Tapered roller bearing 30330-JR-JTEKT - 30330-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30330-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
150	320	72	65	55	837	1080	1200	1500	30330JR					
Dimension series to ISO95 (Refer. I)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
26B	60.8	172	193	302	272	292	12	17	4	3	0.35	1.74	0.96	26.6

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952419916
Inside diameter	150 mm
Outside diameter	320 mm
Thickness	72 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE