

# Tapered roller bearing 32330-R-JTEKT - 32330-R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32330-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |            | Bearing No. <sup>1)</sup> |                |                      |      |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                    | C <sub>r</sub>          | C <sub>0r</sub>      | C <sub>90</sub>      | C <sub>100</sub>     | Grease lub.                          | Oil lub.   |                           |                |                      |      |
| 150                                    | 320                | 114                      | 108                  | 90                   | 1240                    | 1790                 | 1200                 | 1600                 |                                      |            | 32330R                    |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                      |                         |                      |                      |                      |                                      | Constant e | Axial load factors        |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min. | D <sub>1a</sub> max.    | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min. | r <sub>1a</sub> max.                 |            | Y <sub>1</sub>            | Y <sub>0</sub> |                      |      |
| —                                      | 78.4               | 172                      | 187                  | 302                  | 263                     | 298                  | 10                   | 17                   | 4                                    | 3          | 0.35                      | 1.74           | 0.96                 | 42.0 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 4549250233319 |
| Inside diameter  | 150 mm        |
| Outside diameter | 320 mm        |
| Thickness        | 114 mm        |
| Weight           | 42000 g       |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE