

Tapered roller bearing 32932-JR-JTEKT - 32932-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32932-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.		
160	220	38	38	30	295	568	1 500	2 000	32932JR	

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
20C	38.4	172	173	210	204	212	7	8	2	2	0.35	1.73	0.95	4.19

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125713
Inside diameter	160 mm
Inside diameter	6.299" inch
Outside diameter	220 mm
Outside diameter	8.661" inch
Thickness	38 mm
Thickness	1.496" inch
Weight	4190 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE