

Tapered roller bearing 30332-D-JTEKT - 30332-D-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30332-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
160	340	75	68	48	742	933	900	1300			30332D			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	101.8	182	195	322	290	320	9	27	4	3	0.81	0.74	0.41	29.1

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421261
Inside diameter	160 mm
Outside diameter	340 mm
Thickness	75 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE