

Tapered roller bearing 30332-JR-JTEKT - 30332-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30332-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
160	340	75	68	58	938	1220			1 100	1 400	30332JR

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
268	63.3	162	205	322	289	310	12	17	4	3	0.35	1.74	0.96	31.8

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421278
Inside diameter	160 mm
Inside diameter	6.299" inch
Outside diameter	340 mm
Outside diameter	13.386" inch
Thickness	75 mm
Thickness	2.953" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE