

## Tapered roller bearing 32332-JTEKT - 32332-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32332-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
160	340	121	114	95	5	4	1220	1720	1100	1400	32332

  

Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
—	83.0	162	200	322	277	316	10	18	4	3	0.35	1.73	0.95	47.9	

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421285
Inside diameter	160 mm
Outside diameter	340 mm
Thickness	121 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE