

Tapered roller bearing 32036-JR-JTEKT - 32036-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32036-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
180	280	64	64	48	3	2.5	644	1 100	1 200	1 600	32036JR			
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
3FD	59.5	194	199	268	247	268	10	16	2.5	2	0.42	1.42	0.78	14.1

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250267154
Inside diameter	180 mm
Outside diameter	280 mm
Thickness	64 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE