

Tapered roller bearing 30336-D-JTEKT - 30336-D-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30336-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
180	380	83	75	52	833	1150	780	1100	30336D					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
—	112.8	202	225	362	330	351	10	31	4	3	0.81	0.74	0.41	40.1

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421407
Inside diameter	180 mm
Outside diameter	380 mm
Thickness	83 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE