


Tapered roller bearing 32238-JR-JTEKT - 32238-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32238-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾							
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.						
190	340	97	92	75	5	4	1 090	1 740	1 000	1 300	32238JR				
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	S _{2a} min.	S _{2a} max.		r _{1a} min.	r _{1a} max.	
4GD	81.9	212	216	322	286	323	12	22	4	3	0.44	1.38	0.76	36.6	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421537
Inside diameter	190 mm
Outside diameter	340 mm
Thickness	97 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE