

Tapered roller bearing 30338-JTEKT - 30338-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30338-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
190	400	86	78	65	1010	1250	880	1200	30338					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	73.2	218	241	378	342	370	10	20	5	4	0.35	1.73	0.95	46.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421551
Inside diameter	190 mm
Outside diameter	400 mm
Thickness	86 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE