

Tapered roller bearing 32240-JR-JTEKT - 32240-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32240-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
200	360	104	98	82	5	4	1240	1880	960	1300	32240JR			
Dimension series to ISO95 (Refer. I)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. I) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
36D	84.6	222	225	342	302	340	11	22	4	3	0.41	1.48	0.81	44.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124877
Inside diameter	200 mm
Outside diameter	360 mm
Thickness	104 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE