

Tapered roller bearing 32944-JR-JTEKT - 32944-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32944-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|--|-----------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 220 | 300 | 51 | 51 | 39 | 3 | 2.5 | 498 | 1 010 | 1 000 | 1 400 | 32944JR | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | d _{2a} min. | d _{2a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 3EC | 58.6 | 234 | 234 | 288 | 275 | 290 | 9 | 12 | 2.5 | 2 | 0.43 | 1.41 | 0.78 | 10.1 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250125799 |
| Inside diameter | 220 mm |
| Outside diameter | 300 mm |
| Thickness | 51 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE