

Tapered roller bearing 30344-JTEKT - 30344-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30344-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
220	460	97	88	73	1 260	1 680	730	980			30344

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	84.6	248	282	438	386	420	12	23	5	4	0.35	1.73	0.95	69.0

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421698
Inside diameter	220 mm
Outside diameter	460 mm
Thickness	97 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE