

Tapered roller bearing 32952-JR-JTEKT - 32952-JR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32952-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
260	360	63.5	63.5	48	3	2.5	741	1 550	830	1 100	32952JR			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁
3EC	69.6	274	279	348	328	347	11	15.5	2.5	2	0.41	1.48	0.81	18.9

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125805
Inside diameter	260 mm
Outside diameter	360 mm
Thickness	63.5 mm
Weight	18900 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE