

## Tapered roller bearing 1380-1329-JTEKT - 1380-1329-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/1380-1329-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
22.225	53.975	19.368	20.168	14.288	1.6	1.6	36.7	37.9	8 000	11 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
1380	1329	11.6	29.5	29.5	46.0	49.0	1.6	1.6	0.29	2.05	1.13	0.137	0.082

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425467
Inside diameter	22.225 mm
Outside diameter	53.388 mm
Thickness	19.368 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE