

Tapered roller bearing 1755-1729-JTEKT - 1755-1729-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/1755-1729-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
22.225	56.896	19.368	19.837	19.875	1.2	1.2	40.0	43.1	7 600	10 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
1755	1729	12.5	29.0	27.5	49.0	51.0	1.2	1.2	0.31	1.95	1.07	0.150	0.100

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425504
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	56.896 mm
Outside diameter	2.24" inch
Thickness	19.368 mm
Thickness	0.763" inch
Weight	264 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE