

Tapered roller bearing L44640R-L44610-JTEKT - L44640R-L44610-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/l44640r-l44610-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
23.812	50.292	14.224	14.732	10.668	1.6	1.2	31.2	37.0	7 800	10 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
L44640R	L44610	10.8	30.5	28.5	44.5	47.0	1.6	1.2	0.37	1.60	0.88	0.099	0.034

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425559
Inside diameter	23.812 mm
Outside diameter	50.292 mm
Thickness	14.224 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE