

Tapered roller bearing 2687-2631-JTEKT - 2687-2631-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/2687-2631-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|---------------|---------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_1 max. | r_2 max. | C_r | C_{10} | Grease lub. | Oil lub. |
| 25.400 | 66.421 | 23.812 | 25.433 | 19.050 | 1.2 | 1.2 | 67.0 | 75.2 | 6 500 | 8 700 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | Mass (kg) | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|---------------|---------------|----------|--------------------|-------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 2687 | 2631 | 13.9 | 33.5 | 31.5 | 58.0 | 60.0 | 1.2 | 1.2 | 0.25 | 2.36 | 1.30 | 0.272 | 0.163 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952425702 |
| Inside diameter | 25.4 mm |
| Outside diameter | 66.421 mm |
| Thickness | 23.812 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE