


Tapered roller bearing 2682-2631-JTEKT - 2682-2631-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/2682-2631-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_0	C_{10}	Grease lub.	Oil lub.
26.162	66.421	23.812	25.433	19.050	1.6	1.2	67.0	75.2	6 500	8 700

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d_s	d_b	D_s	D_b	$r_{s \text{ max}}$	$r_{b \text{ max}}$		Y_1	Y_2	Inner ring	Outer ring
2682	2631	13.9	34.5	32.0	58.0	60.0	1.6	1.2	0.25	2.36	1.30	0.268	0.163

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425740
Inside diameter	26.162 mm
Outside diameter	66.421 mm
Thickness	23.421 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE