

Tapered roller bearing 14117A-14276-JTEKT - 14117A-14276-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/14117a-14276-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
30.000	69.012	19.845	19.583	15.875	3.6	1.2	46.1	55.0	5 900	7 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
14117A	14276	15.5	42.5	39.5	60.0	63.0	3.6	1.2	0.38	1.57	0.86	0.225	0.135

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425962
Inside diameter	30 mm
Outside diameter	69.012 mm
Thickness	19.845 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE