


Tapered roller bearing 08125-08231-JTEKT - 08125-08231-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/08125-08231-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
31.750	58.738	14.684	15.080	10.716	1.0	1.0	29.5	33.3	6 600	8 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
08125	08231	13.5	37.5	36.0	52.0	55.0	1.0	1.0	0.48	1.26	0.69	0.109	0.056

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426044
Inside diameter	31.75 mm
Outside diameter	58.738 mm
Thickness	14.684 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE