

Tapered roller bearing 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/16137-16284-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r ₁ | r ₂ | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 34.925 | 72.238 | 20.638 | 20.638 | 19.875 | 3.6 | 1.2 | 49.7 | 61.3 | 5 600 | 7 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|----------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 16137 | 16284 | 16.6 | 46.5 | 40.5 | 63.0 | 67.0 | 3.6 | 1.2 | 0.40 | 1.49 | 0.82 | 0.236 | 0.144 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426310 |
| Inside diameter | 34.925 mm |
| Outside diameter | 72.238 mm |
| Thickness | 20.638 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE