

Tapered roller bearing 2796R-2720-JTEKT - 2796R-2720-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/2796r-2720-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_1 min.	C_r	C_{10}	Grease lub.	Oil lub.
34.925	76.200	23.812	25.664	19.050	3.6	3.2	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
2796R	2720	15.9	47.5	41.0	66.0	70.0	3.6	3.2	0.30	1.98	1.09	0.344	0.185

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426365
Inside diameter	34.925 mm
Outside diameter	76.2 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE