

Tapered roller bearing 3478-3420-JTEKT - 3478-3420-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/3478-3420-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|------------------------|------------------------|-------------------------|-----------------|-------------|--------------------------------------|--|
| d | D | T | B | C | r ₁ max. | r ₁ min. | C _r | C ₁₀ | Grease lub. | Oil lub. | |
| 34.925 | 79.375 | 29.370 | 29.771 | 22.812 | 3.6 | 3.2 | 87.4 | 105 | 5 200 | 6 900 | |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|----------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 3478 | 3420 | 20.8 | 50.0 | 43.5 | 67.0 | 74.0 | 3.6 | 3.2 | 0.37 | 1.64 | 0.90 | 0.462 | 0.256 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952426372 |
| Inside diameter | 34.925 mm |
| Outside diameter | 79.375 mm |
| Thickness | 29.37 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE