

Tapered roller bearing 26877R-26822-JTEKT - 26877R-26822-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/26877r-26822-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_a max.	r_b max.	C_r	C_{10}	Grease lub.	Oil lub.
36.512	79.375	23.812	25.400	19.050	0.8	0.8	81.1	105	5 000	6 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
26877R	26822	16.4	44.0	43.0	71.0	74.0	0.8	0.8	0.32	1.88	1.04	0.404	0.186

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426471
Inside diameter	36.512 mm
Inside diameter	1 7/16" inch
Outside diameter	79.375 mm
Outside diameter	3 1/8" inch
Thickness	23.812 mm
Thickness	15/16" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE