

Tapered roller bearing 3878-3820-JTEKT - 3878-3820-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/3878-3820-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	r ₃	C _r	C ₁₀	Grease lub.	Oil lub.
36.512	85.725	30.162	30.162	22.812	0.8	3.2		108	136	4 800	6 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
3878	3820	22.9	48.0	47.0	73.0	81.0	0.8	3.2	0.40	1.49	0.82	0.605	0.285

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426495
Inside diameter	36.512 mm
Outside diameter	85.725 mm
Thickness	30.162 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE