

Tapered roller bearing 13889-13830-JTEKT - 13889-13830-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/13889-13830-jtekt>

Single-row tapered roller bearings
inch series

Koyo

Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub. Oil lub.		
38.100	63.500	12.700	11.908	9.825	1.6	0.8	25.5	33.1	5 800	7 700	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
13889	13830	11.9	45.0	42.5	59.0	60.0	1.6	0.8	0.35	1.73	0.95	0.104	0.045

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426501
Inside diameter	38.1 mm
Inside diameter	1 1/2" inch
Outside diameter	63.5 mm
Outside diameter	2 1/2" inch
Thickness	12.7 mm
Thickness	1/2" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE