

## Tapered roller bearing 28150-28317-JTEKT - 28150-28317-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/28150-28317-jtekt>

Single-row tapered roller bearings Koyo  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub> max.	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
<b>38.100</b>	80.035	21.432	20.940	15.875	1.6	1.6	57.3	65.9	5 300	7 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
<b>28150</b>	<b>28317</b>	16.9	45.5	43.5	69.0	73.0	1.6	1.6	0.40	1.49	0.82	0.285	0.201

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426624
Inside diameter	38.1 mm
Outside diameter	80.035 mm
Thickness	21.432 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE