

Tapered roller bearing 27880-27820-JTEKT - 27880-27820-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/27880-27820-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁ max.	r ₁ min.	C _r	C ₁₀	Grease lub.	Oil lub.
38.100	80.035	24.608	23.698	18.912	0.8	1.6	73.2	91.6	5 200	6 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
27880	27820	22.2	48.0	47.0	68.0	75.0	0.8	1.6	0.56	1.07	0.59	0.378	0.208

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426631
Inside diameter	38.1 mm
Outside diameter	80.035 mm
Thickness	24.608 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE