


## Tapered roller bearing 4375-4335-JTEKT - 4375-4335-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/4375-4335-jtekt>

Single-row tapered roller bearings Koyo  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>1</sub> max.	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.	
<b>38.100</b>	90.488	39.688	40.386	33.336	1.6	3.2	132	189	4 500	6 000	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
<b>4375</b>	<b>4335</b>	25.6	51.0	48.5	77.0	85.0	1.6	3.2	0.28	2.11	1.16	0.841	0.459

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426679
Inside diameter	38.1 mm
Inside diameter	1 1/2" inch
Outside diameter	90.488 mm
Outside diameter	3 9/16" inch
Thickness	39.688 mm
Thickness	1 9/16" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE