

## Tapered roller bearing 344A-332-JTEKT - 344A-332-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/344a-332-jtekt>

Single-row tapered roller bearings  
Inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
40.000	80.000	21.000	22.400	17.826	0.8	1.2	68.0	74.8	4 900	6 600

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
344A	332	15.1	46.0	45.5	73.0	75.0	0.8	1.2	0.27	2.20	1.21	0.334	0.144

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426778
Inside diameter	40 mm
Outside diameter	80 mm
Thickness	21 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE