


Tapered roller bearing 419-414-JTEKT - 419-414-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/419-414-jtekt>

Single-row tapered roller bearings — Koyo
Inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r ₁	r ₂	C _r	C ₁₀	Grease lub.	Oil lub.
41.275	88.501	26.988	29.083	22.225	3.6	1.6	98.2	112	4 900	6 500

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d _a	d _b	D _a	D _b	r _a max.	r _b max.	e	Y ₁	Y ₂	Inner ring	Outer ring
419	414	16.9	54.0	47.0	77.0	80.0	3.6	1.6	0.26	2.28	1.25	0.441	0.325

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426860
Inside diameter	41.275 mm
Outside diameter	88.501 mm
Thickness	26.988 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE