

## Tapered roller bearing 4395-4335-JTEKT - 4395-4335-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/4395-4335-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.	
42.070	90.488	39.688	40.386	33.336	3.6	3.2	132	169	4 500	6 000	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>e</i>	<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>	Inner ring	Outer ring
4395	4335	25.6	58.0	51.0	77.0	85.0	3.6	3.2	0.28	2.11	1.16	0.751	0.459

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952426969
Inside diameter	42.07 mm
Outside diameter	90.488 mm
Thickness	39.688 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE