


Tapered roller bearing 25582-25520-JTEKT - 25582-25520-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/25582-25520-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_r	C_{10}	Grease lub.	Oil lub.
44.450	82.931	23.812	25.400	19.060	5.2	0.8	77.2	100	4 800	6 300

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d_s	d_b	D_s	D_b	$r_{s \text{ max}}$	$r_{b \text{ max}}$		Y_1	Y_2	Inner ring	Outer ring
25582	25520	17.5	59.0	51.0	74.0	77.0	5.2	0.8	0.33	1.79	0.99	0.361	0.200

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427041
Inside diameter	44.45 mm
Outside diameter	82.931 mm
Thickness	23.812 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE