


Tapered roller bearing 33885-33821-JTEKT - 33885-33821-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/33885-33821-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
44.450	95.250	27.783	28.575	22.225	0.8	2.4	108	141	4 100	5 400

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.		<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
33885	33821	20.4	53.0	53.0	85.0	90.0	0.8	2.4	0.33	1.82	1.00	0.714	0.264

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427126
Inside diameter	44.45 mm
Outside diameter	95.25 mm
Thickness	27.783 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE