

# Tapered roller bearing 615-612-JTEKT - 615-612-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/615-612-jtekt>

Single-row tapered roller bearings — Koyo  
inch series



Boundary dimensions (mm)							Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>1</sub> max.	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10v</sub>	Grease lub.	Oil lub.	
44.450	120.650	41.275	41.275	31.760	3.6	3.2	174	217	3 500	4 600	

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
615	612	27.3	62.0	56.0	105.0	110.0	3.6	3.2	0.31	1.91	1.05	1.48	0.853

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427195
Inside diameter	44.45 mm
Outside diameter	120.65 mm
Thickness	41.275 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE