


Tapered roller bearing 25590-25526-JTEKT - 25590-25526-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/25590-25526-jtekt>

Single-row tapered roller bearings ————— **Koyo**
inch series



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
45.618	85.000	23.812	25.400	19.060	3.6	2.4	77.2	100	4 800	6 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Con-stant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
25590	25526	17.5	58.0	51.0	74.0	78.0	3.6	2.4	0.33	1.79	0.99	0.344	0.241

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427294
Inside diameter	45.618 mm
Inside diameter	1.796" inch
Outside diameter	85 mm
Outside diameter	3.346" inch
Thickness	23.812 mm
Thickness	15/16" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE